

# Polyfleece SX<sup>®</sup> 1000 adhesive tape

## TECHNICAL DATASHEET

Status 13.12.2021

Item no. S01902075

### PROPERTIES

**Polyfleece SX<sup>®</sup> 1000 adhesive tape 75 mm** is an adhesive tape product especially developed for customers enquiries aligning in an extremely high flexibility to **Polyfleece SX<sup>®</sup> 1000** - rolls.

### APPLICATION

**Polyfleece SX<sup>®</sup> 1000 adhesive tape 75 mm** acts as a reliable and durable waterproofing seam in between two **Polyfleece SX<sup>®</sup> 1000** - rolls. The protective liner will be removed after the **Polyfleece SX<sup>®</sup> 1000** - rolls have been positioned in place.

### TECHNICAL DATA



01 / coating

HDPE-foil, 125 µm, blue,

both-sided covered with silicone

02 / adhesive film

high quality acrylic resin-based adhesive

thickness of film: 0,80 mm

Temperature range of application: -40°C to > +120°C, for a short period up to +160°C

# Polyfleece SX<sup>®</sup> 1000 adhesive tape

## TECHNICAL DATASHEET

Status 13.12.2021

Item no. S01902075

### PACKAGING & STORAGE

Respecting an appropriate storage (room temperature 20°C, air humidity 50%) **Polyfleece SX<sup>®</sup> 1000 adhesive tape 75 mm** can be installed within the next 12 months without any significant material changes.

### INSTALLATION

**Polyfleece SX<sup>®</sup> 1000 adhesive tape 75 mm** on the long seam is preassembled onto the **Polyfleece SX<sup>®</sup> 1000** - rolls. After the **Polyfleece SX<sup>®</sup> 1000** - rolls have been positioned in place the protective liner will be removed. On the cross seams **Polyfleece SX<sup>®</sup> 1000 adhesive tape 75 mm** will be assembled on site. The seams have to be carried out according to our installation guidelines.

### ACCESSORIES

Order no S01102010	Polyfleece SX1000 roll 20 m
Order no S01202010	Polyfleece SX1000 wall roll 20 m
Order no S02410290	Polymer-swellingpaste SX <sup>®</sup> 100 cartridge 290 ml
Order no S01900025	Polyfleece SX <sup>®</sup> 1000 – fleece tape 80mm L=25m

Note:

The information on this data sheet is based on our experience and given to the best of our knowledge, but is not legally binding. Recommendations, which are at variance with those stated in this data sheet, are only binding for us, when confirmed in writing. The manufacturer is not responsible for damages resulting from the misuse or incorrect storage of the product. For the accuracy of this information we are liable within the scope of our delivery and service conditions. Creation date: 12/2021