

### TECHNICAL DATASHEET

Stand: 25.02.2021

Item no. S07502025

### PROPERTIES

an.kox **Press seal** is an advanced waterbar based on butyl with fantastic long-term behavior. an.kox **Press seal** remains ductile. It distinguishes itself by its high adhesion properties especially on concrete. an.kox **Press seal** is highly resistant against UV and Ozone but also against many chemical substances. an.kox **Press seal** does not shrink, it does not crack and there is no swelling in contact with water.

### APPLICATION

an.kox **Press seal** can be applied in prefab joints, in between concrete pipes or as sealing in man holes. For the installation no primer is required. On many surfaces an.kox **Press seal** is self adhesive.

### TECHNICAL DATA

Profile:	20 x 25 mm
Color:	black
Consistency:	ductile

### PACKAGING & STORAGE

20 x 25 mm - profile	box: 20 m (5 rolls à 4 m)	Palette: 30 boxes = 600 m
----------------------	---------------------------	---------------------------

Unlimited storable in a cool and dry environment.

### INSTALLATION

With hardened concrete substrates must be firm and load bearing, as well as free from dust, grease, oils and other separating materials. The substrate must be dry during assembly. A preliminary coat (**Contact adhesive SuperX 1** or **Polymer-Quellpaste SX® 100**) is to be applied in order to keep an.kox **Press seal** in place. The substrate can preferably be equalized by means of **Polymer-Quellpaste SX® 100**.

an.kox **Press seal** is installed on one joint flank. The other joint flank is then gently pushed into an.kox **Press seal**.

an.kox **Press seal** can easily and without any risk be applied in the concrete edge zone, due the fact that there is no swelling activity in contact with water.

# Press seal

## Butyl waterbar

### TECHNICAL DATASHEET

Stand: 25.02.2021

Item no. S07502025

### ACCESSORIES

Item no. S02830290	Contact adhesive SuperX 1 cartridge 290 ml
Item no. S02830291	Contact adhesive SuperX 1 PLUS cartridge 290 ml
Item no. S02410290	Polymer-swellingpaste SX® 100

Note:

The information on this data sheet is based on our experience and given to the best of our knowledge, but is not legally binding. Recommendations, which are at variance with those stated in this data sheet, are only binding for us, when confirmed in writing. The manufacturer is not responsible for damages resulting from the misuse or incorrect storage of the product. For the accuracy of this information we are liable within the scope of our delivery and service conditions. Creation date: 02/2021